Röchling Industrial

Röchling Industrial SE & Co. KG • Post-box 12 49 • D-49724 Haren/Germany

Access Plastics LTD
Unit 16, Ashbourne Ind. Estate
County Meath
Irland

Quality management
Johannes Mohs
Tel. +49 5934 701-218
Abt. Fax +49 5934 701-299
Pers. Fax +49 5934 701-611 218
jmohs@roechling.com

Product information
Declaration of Performance

24. April 2026/GH

Material: Trovidur® EC Clad

PVC-U sheets
Thickness: 2,30 mm
Lengths: 2440 to 3050 mm
Width: 1220 mm
Colour: White and multiple colours

Dear Ladies and Gentlemen,

hereby we inform you, that our material Trovidur® EC Clad is produced according to the international standard DIN EN ISO 11833-1- it meets the following characteristics:

Parameter	Standard	Classification	Harmonised European Standard
Reaction to fire	EN 13501-1	B s3 d0	DIN EN ISO 11833-1
Release VOC´s	ISO 16000	None	
Notched impact resistance	DIN EN ISO 179	>4 kJ/m²	
Working temperature	na	-15…+60 °C	

This information was provided by machine and requires therefore no signature.

Röchling Industrial SE & Co. KG

Quality management

Advice: This product information serves alone for informative purposes. Warranties, assurances and guarantees cannot be derived from this.